


D7044M Multiplex mini single-input module, 12V

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Use with FPD-7024, D7024, or DS9400M addressable FACPs
- ▶ Fits into a standard single-gang back box
- ▶ Easy addressing using rotary switches
- ▶ Low current draw

The D7044M MUX mini single-input module (12V) connects a normally-open (NO) contact to the multiplex bus of an FPD-7024, D7024, or DS9400M Addressable fire alarm control panel (FACP). Use the module's supervised input in a Class B configuration. All operating power for the input module is drawn from the FACP. Rotary switches allow convenient address setting.



Notice

The D7024 and DS9400M FACPs are legacy products listed to UL864, 8th edition.

Certifications and approvals

Region	Regulatory compliance/quality marks	
USA	UL	UL 864, Control Units and Accessories for Fire Alarm Systems
	FM	see the FM Approval Guide
	CSFM	see www.boschsecurity.com (the Bosch website)
	FDNY-CoA	6173

Installation/configuration notes

Compatible Products

The D7044 is compatible with the FPD-7024 and D7024* Fire alarm control panels. The modules connect to the FACP through an expansion module. Use the FPE-7039 with the FPD-7024 FACP or the D7039* with either the FPD-7024 or D7024* FACPs. The DS9400M* includes the expansion module. * indicates legacy products.

The FPD-7024 panels and the FPE-7039 expansion module are listed to UL864, 10th edition. The D7039 expansion module is listed to UL864, 9th edition. The D7024 and DS9400M panels are listed to UL864, 8th edition.

Mounting

The module fits in a single-gang back box to which the device it is monitoring is attached.

Wiring

Connections for the module are made using the 16 AWG (ISO 1.5 mm²) flying leads from the device. All wiring is power limited and supervised.



Notice

Do not use shielded wire.

**Notice**

Supervise the input loop with the supplied EOL resistor.

Parts included

Quantity	Component
1	D7044M module
1	2.21 kΩ end-of-line (EOL) resistor (P/N: F.01U.034.504)
1	Literature pack

Technical specifications**Electrical**

Circuit Designation MUX Bus Input	Supervised Class A SLC or Class B SLC Supervised Class B IDC
Input Type	One normally-open (NO) contact input supervised by a 2.21 kΩ EOL resistor (P/N: F.01U.034.504)
Power supplied from FACP's MUX bus	0.55 mA 8 V peak (12 VDC nominal)

Current
Voltage
(minimum)

Environmental

Environment	Indoor, dry
Relative Humidity	Up to 93% non-condensing
Temperature (operating)	+32°F to +120°F (0°C to +49°C)

Mechanical

Color	White
Dimensions (L x W x H)	12 cm (4.7 in.) x 5 cm (1.97 in.) x 5 cm (1.97 in.)
Mounting	Standard double-gang box
Material	ABS plastic
Weight	
Gross	0.090 kg (3.17 oz.)
Net	0.075 kg (2.65 oz.)

Ordering information**D7044M Multiplex mini single-input module, 12V**

Connects a normally-open (NO) contact to the multiplex bus of an FPD-7024, D7024, or DS9400M FACP's.

Order number **D7044M**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Germany
www.boschsecurity.com

North America:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia