



LIFE SAFETY
CONSULTANTS



Special Application Manual Alarm Stations

Description

These die-cast, metal pull stations are designed to meet special application requirements such as: weather alert, hazmat spills, police call, medical emergencies, door release and fire suppression. There is a series of special application labels to designate the function of the pull station for the user. There is no agency standard, outside of red for fire that dictates what color is to be used for a specific application.

This series of pull stations is available in single or dual action configurations. There are two sets of gold plated contacts that can be configured by the installer as either normally open or normally closed. The terminal block accommodates field wiring of #22 to #14 AWG. All models have been tested by UL and found in compliance with the pull force requirements of the Americans with Disabilities Act (ADA). The special application stations are key resettable.

Operation

The stations are operated by pulling the handle marked "PULL" on the front of the unit as far down as it will go. At that point, the handle will lock in place and is easily visible from up to 50 feet. The activation handle is reset by opening the station with the key, placing the "PULL" handle to its normal upright position and relocking the station. On the dual action, the "PUSH" or optional "EMERGENCY" bar moves inward allowing the "PULL" handle to be operated by a single hand.

Mounting Configurations

Semi-Flush--All models mount on a standard single-gang back-box.

Surface Mount Interior--Use SGB-32S

Surface Mount Exterior-- Use die cast weatherproof back-box #SG-WP series. Includes gasket set, final assembly achieves NEMA 3R rating.

- **Single or Dual Action**
- **Special Application Labeling Available**
- **Screw Terminal Connections**
- **Normally Open or Closed Alarm/ Auxiliary Contacts**
- **Gold Plated Contacts**
- **Surface or Weatherproof Back-box**



LIFE SAFETY
CONSULTANTS

Life Safety Consultants

al Coast a ay Suite
Palm Coast, FL 32137

Tel# (888) 557-0558 • Fax (616) 656-1807

www.lifesafetycom.com

Special Application Manual Pull Stations

SPECIFICATIONS

Listings:	UL, ULC, FM, CSFM, MEA
Temperature:	-40 ^o to 150 ^o F; 40 ^o to 65 ^o C, 90% relative humidity @ 100 ^o F; 38 ^o C
Switch Rating:	2 Amps @ 125 VDC, 2 Amps @ 240 VAC,
Screw Terminal Block	#22 to #14 gauge wire
Pull Station Weight:	1.2 lbs., 0.55 kg
Pull Station Dimensions:	4.75" h x 3.25" w x 1.1" d; 12.1 x 8.3 x 2.8 cm
Surface-Mount Backbox Dims:	Outside: 4.75" h x 3.25" w x 2.25" d; 12.1 x 8.3 x 5.7 cm Inside Depth: 2.12"; 5.4 cm
Lock:	CAT30 aka "B" key lock is standard (others available, call for options)
Break-Rod:	Optional, not required for operation. One break-rod is included with each pull station

ORDERING INFORMATION

Color Pull Stations

- SG-42CXX1-BL Dual Action Pull Station, DPDT, Blue
- SG-42CXX1-GR Dual Action Pull Station, DPDT, Green
- SG-42CXX1-YL Dual Action Pull Station, DPDT, Yellow
- SG-42CXX2-BL Single Action Pull Station, DPDT, Blue
- SG-42CXX2-GR Single Action Pull Station, DPDT, Green
- SG-42CXX2-YL Single Action Pull Station, DPDT, Yellow



Dual Action with Emergency Bar

- SG-42CXX1E-BL Dual Action Pull Station, with Emergency Push Bar, DPDT, Blue
- SG-42CXX1E-GR Dual Action Pull Station, with Emergency Push Bar DPDT, Green
- SG-42CXX1E-YL Dual Action Pull Station, with Emergency Push Bar DPDT, Yellow

Special Application Pull Station Back-Boxes

Sheet Metal Back-Box, Indoor Use, two - 1/2" knockouts,

For BLUE order SGB-32S-BL; For YELLOW order SGB-32S-YL, for GREEN order SGB-32S-GR

Weather Proof Back-Box, Outdoor Use, NEMA 3R, with gasket, one tapped hole 3/4" NPT

For BLUE order SG-WP-BL; For Yellow order SG-WP-YL, for GREEN SG-WP-GR



Sheet Metal Back-Box

Accessories for Pull Station

- SG-GR01 Replacement Break-Rods (12 per package)
Notes: • One (1) break-rod is included with each pull station;
• Break-rod is optional, it is not required for operation
- SG-LOCK-* Alternate lock set (* Consult Factory for options), CAT15, CAT45, CAT60, Hex,

Weather- Proof Cast Metal Back-Box Shown with Gasket



Life Safety Consultants
 250 Palm Coast Parkway NE, Suite 607 # 323
 Palm Coast, FL 32137
 Tel# (888) 557-0558 Fax (616) 656-1807
www.lifesafetycom.com

Labels for Special Application Pull Stations

Please select one (1) top label and one (1) bottom label per pull station.

Labels for Top Section

Part #	Label Color	Text Color	Text
880-0046-B	Blue	White	ALARM ALARM
880-0047-B	Blue	White	ALERT ALERT
880-0050-B	Blue	White	OPEN DOOR
880-0050-C/R	Clear	Red	OPEN DOOR
880-0050-C/W	Clear	White	OPEN DOOR
880-0046-G	Green	White	ALARM ALARM
880-0047-G	Green	White	ALERT ALERT
880-0046-Y	Yellow	Red	ALARM ALARM
880-0047-Y	Yellow	Red	ALERT ALERT
880-0048-Y	Yellow	Red	LOCAL EVAC
880-0050-Y	Yellow	Red	OPEN DOOR

Examples



#880-0047-G and #880-0055-G



#880-0046-Y and #880-0052-Y



#880-0047-B and #880-0057-B

Labels for Lower Section

Part #	Label Color	Text Color	Text
880-0056-B	Blue	White	MEDICAL
880-0057-B	Blue	White	TORNADO
880-0058-B	Blue	White	DOOR RELEASE
880-0062-B	Blue	White	POLICE
880-0090-C/R	Clear	Red	EMERGENCY EXIT
880-0090-C/W	Clear	White	EMERGENCY EXIT
880-0055-G	Green	White	EMERGENCY
880-0056-G	Green	White	MEDICAL
880-0052-Y	Yellow	Red	HAZMAT
880-0053-Y	Yellow	Red	AFFF RELEASE
880-0054-Y	Yellow	Red	EVACUATE
880-0055-Y	Yellow	Red	EMERGENCY
880-0056-Y	Yellow	Red	MEDICAL
880-0057-Y	Yellow	Red	TORNADO
880-0058-Y	Yellow	Red	DOOR RELEASE
880-0199	Yellow	Red	FOAM
Multiple Label Set			
880-0101	Yellow	Red	MANUAL RELEASE SUPPRESSION RELEASE EXTINGUISHER RELEASE SPRINKLER RELEASE



LIFE SAFETY
CONSULTANTS

Life Safety Consultants

250 Palm Coast Parkway NE, Suite 607 # 323

Palm Coast, FL 32137

Tel# (888) 557-0558 Fax# (616) 656-1807

www.lifesafetycom.com