Specifications







Eaton E60-W

Eaton Wheelock E50/E60 speaker, ceiling, white, no lettering, 25/70V, indoor

General specifications	
PRODUCT NAME	Eaton Wheelock E50/E60 speaker
CATALOG NUMBER	E60-W
UPC	786697137457
PRODUCT LENGTH/DEPTH	0.83 in
PRODUCT HEIGHT	7.36 in
PRODUCT WIDTH	7.36 in
PRODUCT WEIGHT	1.382 lb
COMPLIANCES	Not Applicable



Product specifications		
COMPLIANCE AND STANDARDS	FCC CSFM UL	
MOUNTING METHOD	Ceiling	
HOUSING COLOR	White	
HOUSING MATERIAL	UV stabilized plastic	
FREQUENCY RANGE - MAX	4000 Hz	
FREQUENCY RANGE -	400 Hz	
TAPS (SELECTABLE)	1/8 watt -2 watts: 1/8, 1/4 , 1/2 , 1 , 2	
LETTERING	No lettering	
OPERATING TEMPERATURE	33.8°F to 120.2°F (0°C to 49°C) & maximum humidity of 93%	
INDOOR/OUTDOOR	Indoor	
VOLTAGE	25 V 70 V	
SOUND LEVEL (DBA)	Up to 87 dB at 10 ft: 77,79.5,82.5,85,88	

Resources	
BROCHURES	Wheelock EH high fidelity speaker brochure
CATALOGS	Wheelock life safety notification appliances catalog CA450003FR, French Canadian
	Wheelock life safety notification appliances catalog CA450002EN, Canada
DRAWINGS	wheelock-e60-ceiling- speaker-drawing
	wheelock-e50-wall- speaker-drawing
INSTALLATION INSTRUCTIONS	wheelock-e50-wall- speaker-install-sheet- P84590
	wheelock-e60h-speaker- install-sheet-P85325
	wheelock-e50h-speaker- install-sheet-P85324
	Wheelock E60 speaker install sheet P84719
SELLING POLICY AND T&CS	Wheelock E50, E60, E70, E90 UL Listings
	Wheelock E speakers CSFM listing
	Wheelock E60H, E70H, E90H speaker CSFM listing
	Wheelock E50 speaker CSFM listing
	Wheelock E50, E50H speaker UL listing
SPECIFICATIONS AND DATASHEETS	<u>Eaton Specification Sheet -</u> <u>E60-W</u>
TECHNICAL DATA SHEETS	wheelock-mounting- accessories-data-sheet
	wheelock-e50h-e60h- speakers-strobes-data- sheet-TD450017EN
	wheelock-e50e60- speakers-strobes-data- sheet-TD450023EN

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









