

Specifications



Photo is representative



Eaton ELFHNW

Eaton Eluxa low frequency sounder, wall, white, FIRE, 24V indoor

General specifications

PRODUCT NAME	Eaton Eluxa low frequency sounder and sounder strobe
CATALOG NUMBER	ELFHNW
UPC	786697009730
PRODUCT LENGTH/DEPTH	2.63 in
PRODUCT HEIGHT	6.35 in
PRODUCT WIDTH	4.56 in
PRODUCT WEIGHT	1.2 lb
COMPLIANCES	Not Applicable

Product specifications

TYPE	Sounder
COMPLIANCE AND STANDARDS	UL ULC FCC RoHS
MOUNTING METHOD	Wall
HOUSING COLOR	White
VOLTAGE	24 V
AUDIBLE CURRENT	0.098 mA
LETTERING	FIRE
OPERATING TEMPERATURE	32°F to 122°F (0°C to 50°C)
INDOOR/OUTDOOR	Indoor
520 HZ MODES OF OPERATION	Continuous T3 (fire) T3/T4 Sync Control
APPLICATION	Sleeping areas

Resources

BROCHURES	Eluxa family brochure
COMPLIANCE INFORMATION	Eluxa UL listing
	Eluxa low frequency sounder wall drawing
DRAWINGS	Eluxa low frequency sounder strobe wall drawing
INSTALLATION INSTRUCTIONS	Eluxa low frequency sounder wall install sheet P85753 Eluxa low frequency sounder ceiling install sheet P85759
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - ELFHNW
TECHNICAL DATA SHEETS	Eluxa low frequency sounders data sheet wheelock-mounting-accessories-data-sheet

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

