

Specifications



Eaton ELFHSRC

Eaton Eluxa low frequency sounder strobe, ceiling, red, FIRE, 110/177 cd, 24V, indoor

General specifications

PRODUCT NAME	Eaton Eluxa low frequency sounder and sounder strobe
CATALOG NUMBER	ELFHSRC
UPC	786697009785
PRODUCT HEIGHT	3.52 in
PRODUCT DIAMETER	6.3 in
PRODUCT WEIGHT	1.2 lb
COMPLIANCES	Not Applicable

Product specifications

TYPE	Sounder strobe
COMPLIANCE AND STANDARDS	UL ULC FCC RoHS
MOUNTING METHOD	Ceiling
HOUSING COLOR	Red
LENS COLOR	Clear
LENS MATERIAL	Lexan
LAMP TYPE	LED
CURRENT DRAW (DC)	<ul style="list-style-type: none">• 0.164• 0.256
VOLTAGE	24 V
LETTERING	FIRE
OPERATING TEMPERATURE	32°F to 122°F (0°C to 50°C)
INDOOR/OUTDOOR	Indoor
CANDELA SETTINGS	110 cd 177 cd
520 HZ MODES OF OPERATION	Continuous T3 (fire) T3/T4 Sync Control
APPLICATION	Sleeping areas

Resources

BROCHURES	Eluxa family brochure
COMPLIANCE INFORMATION	Eluxa UL listing
DRAWINGS	Eluxa low frequency sounder strobe wall drawing Eluxa low frequency sounder wall drawing
INSTALLATION INSTRUCTIONS	Eluxa low frequency sounder ceiling install sheet P85759 Eluxa low frequency sounder wall install sheet P85753
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - ELFHSRC
TECHNICAL DATA SHEETS	Eluxa low frequency sounders data sheet wheelock-mounting-accessories-data-sheet

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

