Specifications







Eaton ELSPKR

Eaton Eluxa high fidelity speaker, wall, red, FIRE, clear lens, 25/70V, indoor

General specifications		
PRODUCT NAME	Eaton Eluxa high fidelity speaker	
CATALOG NUMBER	ELSPKR	
UPC	786697009600	
PRODUCT LENGTH/DEPTH	2.94 in	
PRODUCT HEIGHT	6.35 in	
PRODUCT WIDTH	4.56 in	
PRODUCT WEIGHT	1.44 lb	
COMPLIANCES	Not Applicable	



Product specifications	
MOUNTING METHOD	Wall
HOUSING COLOR	Red
INDOOR/OUTDOOR	Indoor
HOUSING MATERIAL	Plastic
LETTERING	FIRE
VOLTAGE	70 V 25 V
OPERATING TEMPERATURE	32°F to 122°F (0°C to 50°C)
COMPLIANCE AND STANDARDS	UL ULC

Resources	
BROCHURES	Eluxa family brochure
	Eluxa product cross reference
DRAWINGS	Eluxa speaker wall drawing
	Eluxa speaker ceiling drawing
INSTALLATION INSTRUCTIONS	Eluxa speaker ceiling install sheet P85758
	Eluxa installation instructions speaker strobe p85967a clear amber wall
	Eluxa speaker wall install sheet P85757
SELLING POLICY AND T&CS	Eluxa UL listing
SPECIFICATIONS AND DATASHEETS	<u>Eaton Specification Sheet -</u> <u>ELSPKR</u>
TECHNICAL DATA SHEETS	wheelock-mounting- accessories-data-sheet
	Eluxa high fidelity speaker and speaker strobe data sheet; TD450158EN

Speaker specifications		
FREQUENCY RANGE - MIN	300 Hz	
FREQUENCY RANGE - MAX	8000 Hz	
SOUND LEVEL (DBA)	75/79/82/85/87	
TAPS (SELECTABLE)	1/8, 1/4, 1/2, 1, 2	

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









