

Specifications

Eaton ELSPKRC

Eaton Eluxa high fidelity speaker, ceiling, red, FIRE, clear lens, 25/70V, indoor

General specifications

PRODUCT NAME	Eaton Eluxa high fidelity speaker
CATALOG NUMBER	ELSPKRC
UPC	786697009617
PRODUCT HEIGHT	6.25 in
PRODUCT DIAMETER	1.5 in
PRODUCT WEIGHT	1.48 lb
COMPLIANCES	Not Applicable

Product specifications

MOUNTING METHOD	Ceiling
HOUSING COLOR	Red
INDOOR/OUTDOOR	Indoor
HOUSING MATERIAL	Plastic
LETTERING	FIRE
VOLTAGE	70 V 25 V
OPERATING TEMPERATURE	32°F to 122°F (0°C to 50°C)
COMPLIANCE AND STANDARDS	UL ULC

Resources

BROCHURES [Eluxa family brochure](#)

[Eluxa product cross reference](#)

DRAWINGS [Eluxa speaker wall drawing](#)

[Eluxa speaker ceiling drawing](#)

[Eluxa speaker wall install sheet P85757](#)

INSTALLATION INSTRUCTIONS [Installation instructions eluxa horn strobe clear and amber lens ceiling mount](#)

[Eluxa speaker ceiling install sheet P85758](#)

SELLING POLICY AND T&CS [Eluxa UL listing](#)

SPECIFICATIONS AND DATASHEETS [Eaton Specification Sheet - ELSPKRC](#)

TECHNICAL DATA SHEETS [wheelock-mounting-accessories-data-sheet](#)
[Eluxa high fidelity speaker and speaker strobe data sheet; TD450158EN](#)

Speaker specifications

FREQUENCY RANGE - MIN	300 Hz
FREQUENCY RANGE - MAX	8000 Hz
SOUND LEVEL (DBA)	75/79/82/85/87
TAPS (SELECTABLE)	1/8, 1/4, 1/2, 1, 2

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

