

Specifications



Photo is representative



Eaton ELSPKW-N

Eaton Eluxa high fidelity speaker, wall, white, no lettering, clear lens, 25/70V, indoor

General specifications

PRODUCT NAME	Eaton Eluxa high fidelity speaker
CATALOG NUMBER	ELSPKW-N
PRODUCT LENGTH/DEPTH	6.35 in
PRODUCT HEIGHT	4.56 in
PRODUCT WIDTH	2.94 in
PRODUCT WEIGHT	1.44 lb
COMPLIANCES	Not Applicable

Product specifications

MOUNTING METHOD	Wall
HOUSING COLOR	White
INDOOR/OUTDOOR	Indoor
HOUSING MATERIAL	Plastic
LETTERING	No lettering
VOLTAGE	70 V 25 V
OPERATING TEMPERATURE	32°F to 122°F (0°C to 50°C)
COMPLIANCE AND STANDARDS	UL ULC

Speaker specifications

FREQUENCY RANGE - MIN	300 Hz
FREQUENCY RANGE - MAX	8000 Hz
SOUND LEVEL (DBA)	75/79/82/85/87
TAPS (SELECTABLE)	1/8, 1/4, 1/2, 1, 2

Resources

BROCHURES	Eluxa family brochure
DRAWINGS	Eluxa speaker wall drawing Eluxa speaker ceiling drawing
INSTALLATION INSTRUCTIONS	Eluxa speaker wall install sheet P85757 Eluxa speaker ceiling install sheet P85758
SELLING POLICY AND T&CS	Eluxa UL listing
TECHNICAL DATA SHEETS	wheelock-mounting-accessories-data-sheet

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

