

# Specifications



## Eaton ELSPSTRC

Eaton Eluxa high fidelity speaker strobe, LED, ceiling, red, FIRE, clear lens, 15/30/75/110/150/177 cd, 25/70V, indoor

### General specifications

<b>PRODUCT NAME</b>	Eaton Eluxa high fidelity speaker strobe
<b>CATALOG NUMBER</b>	ELSPSTRC
<b>UPC</b>	786697009655
<b>PRODUCT HEIGHT</b>	3.64 in
<b>PRODUCT DIAMETER</b>	6.2 in
<b>PRODUCT WEIGHT</b>	1.86 lb
<b>COMPLIANCES</b>	Not Applicable

## Product specifications

<b>MOUNTING METHOD</b>	Ceiling
<b>HOUSING COLOR</b>	Red
<b>INDOOR/OUTDOOR</b>	Indoor
<b>HOUSING MATERIAL</b>	Plastic
<b>LETTERING</b>	FIRE
<b>VOLTAGE</b>	24 V 25 V 70 V
<b>OPERATING TEMPERATURE</b>	32°F to 122°F (0°C to 50°C)
<b>COMPLIANCE AND STANDARDS</b>	UL ULC FCC

## Speaker specifications

<b>FREQUENCY RANGE - MIN</b>	300 Hz
<b>FREQUENCY RANGE - MAX</b>	8000 Hz
<b>SOUND LEVEL (DBA)</b>	75/79/82/85/87
<b>TAPS (SELECTABLE)</b>	1/8, 1/4, 1/2, 1, 2

## Strobe specifications

<b>LAMP TYPE</b>	LED
<b>CANDELA SETTINGS</b>	15 cd 30 cd 75 cd 95 cd 150 cd 177 cd
<b>CURRENT DRAW (DC)</b>	<ul style="list-style-type: none"><li>• 0.022</li><li>• 0.030</li><li>• 0.060</li><li>• 0.086</li><li>• 0.125</li><li>• 0.185</li></ul>
<b>LENS COLOR</b>	Clear
<b>LENS MATERIAL</b>	Lexan

## Resources

<b>BROCHURES</b>	<a href="#">Eluxa family brochure</a>
<b>COMPLIANCE INFORMATION</b>	<a href="#">Eluxa UL listing</a>
<b>DRAWINGS</b>	<a href="#">Eluxa speaker strobe ceiling drawing</a> <a href="#">Eluxa speaker strobe wall drawing</a>
<b>INSTALLATION INSTRUCTIONS</b>	<a href="#">Eluxa speaker ceiling install sheet P85758</a> <a href="#">Eluxa speaker wall install sheet P85757</a>
<b>SPECIFICATIONS AND DATASHEETS</b>	<a href="#">Eaton Specification Sheet - ELSPSTRC</a>
<b>TECHNICAL DATA SHEETS</b>	<a href="#">wheelock-mounting-accessories-data-sheet</a>

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

