

Macurco™

BUILDING & HOME SOLUTIONS

Whether you are looking for gas detection for a security system, building automation or HVAC system, for personal safety or for monitoring specific gases in potentially hazardous environments, Macurco has a gas detector to meet your needs.



Commercial Series

6-Series (12-24V) & 12-Series (120V) Fixed Gas Detectors



Grey Housing (Standard)



White Housing Option

The Macurco 6 & 12 Series fixed gas detectors provide life-saving solutions aimed to protect people and property. These fixed gas detectors are designed for low level detection, mitigation, and notification. Let these detectors do the work for you by shutting off valves, turning on fans, engaging horns and strobes, and provide notification to fire panels and building automation systems when gases reach key limits.

Key Features


- Easy installation to 4x4 electrical boxes via mud plate
- User selectable settings (Default to industry standards) via two button interface
- 5 A SPDT fan relay, 0.5A alarm relay to control fans, valves, louvers, horn and strobes
- 4-20mA output to control VFD's and send to BMS
- LED display to easily show gas concentrations
- End of life notification
- Field calibration kits available

Applications

- Parking Garages
- Mechanical Rooms
- Restaurants
- Battery Charging Stations
- Breweries
- Storage Facilities
- Loading Docks
- Warehouses
- Firehouses & Ambulance Bays
- Refrigeration Facilities
- Vehicle Repair Facilities
- Bus Depots

Commercial Series

Specifications

Size	4 1/2 x 4 x 2 1/8 in. (11.4 X 10.2 X 5.4 cm)
Weight	1 pound (0.45 kg)
Voltage/Current	6-Series Power: 3 W (max) from 12 to 24 VAC or 12 to 32 VDC :Current @ 24 VDC: 75 mA in alarm, 50 mA fan relay on and 23 mA stand by 12-Series Power: 100-240 VAC (50 to 60 HZ) Current: 1.0 A MAX
Operating Temperature	0°F to 125°F (-18°C to 52°C) CD-6/12H 32°F to 122°F (0°C to 50°C)
Ambient Humidity	10-90% RH NonCondensing
Display	LED (can turn on/off)
Current Loop	Analog 4-20mA, with MRS-485 Adapter Digital Modbus
Mounting	4" x 4" electrical box
Relays	5A Fan Relay & 0.5A Alarm Relay User Adjustable Settings
Certifications	ETL Listed  *See detector manual for additional certifications
Warranty	Two Year Limited Warranty

Accessories

Name	Model Number
Control Panels	DVP-120, DVP-120M, DVP-120B
Addressable Adapter	MRS-485
Horn and Strobe (5 color options)	HS-A, HS-B, HS-R, HS-G, HS-C
Duct Mount Kit	DMK-1
Weatherproof Housing Kit	WHK-1
Plug in 24VDC Transformer	PS-24
Calibration Kits	Based on Gas Type



Control Panels



Addressable Adapter



Horn and Strobe



Calibration Kits



Weatherproof Housing Kit
(Detector sold separately)

Model Number	Gas Type	Range (Units)	Low Level Alarm Adjustable (Default)	High Level Alarm Adjustable (Default)	Sensor Life	Recommended Coverage Area
CX-6 CX-12	Carbon Monoxide (CO) & Nitrogen Dioxide (NO ₂)	Refer to CM-6 & TX-6ND	Refer to CM-6 (CO) & TX-6-ND (NO ₂)	Refer to CM-6 (CO) & TX-6-ND (NO ₂)	2 Years**	Refer to CM-6 & TX-6ND
CM-6 CM-12	Carbon Monoxide (CO)	200 PPM	0, 15, 25, 35, 50 or 100 PPM	0, 50, 100, 150 or 200 PPM	7 Years	5,000 sq. ft.
GD-6 GD-12	Propane (LP) Methane (NG) Hydrogen (H ₂)	0-50% LEL	0, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20% LEL	OFF, 5, 10, 15, 20, 25% LEL	5 Years	900 sq. ft.
TX-6-ND TX-12-ND	Nitrogen Dioxide (NO ₂)	0-20 PPM	0, 0.5, 0.7, 1.0, 1.2, 1.5, 1.7, 2.0, 2.2, 2.5, 2.7, 3.0, 3.2, 3.5, 3.7, 4.0, 4.2, 4.5, 4.7, 5.0 PPM	0-20 PPM, (5 PPM default)	2 Years**	5,000 sq. ft.
TX-6-HS TX-12-HS	Hydrogen Sulfide (H ₂ S)	0-50 PPM	0, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20 PPM	0, 5, 10, 15, 20, 25, 30, 35, 40, 45, 50 PPM	2 Years**	900 sq. ft.
TX-6-AM TX-12-AM	Ammonia (NH ₃)	0-100 PPM	0, 15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, or 75 PPM	0, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95 or 100 PPM	2 Years**	900 sq. ft.
OX-6 OX-12	Oxygen (O ₂)	0-25 % V/V	0, 18, 18.1... , 20.2, 20.3, 20.4 & 20.5% v/v & high 23.5 % v/v (preset)	0, 18.5, 19, 19.5, 20, 20.5 and high 23.5 % v/v (preset)	2 Years**	900 sq. ft.
RD-6 RD-12	Refrigerant (R-22, R-134A, R-404A, R-407C, R-410A)	0-1,000 PPM	0, 100, 150, 200, 250, 300, 350 PPM	0, 100, 125, 150, 200, 300, 400, 500 or 600 PPM	7 Years	900 sq. ft.
CD-6H CD-12H (Auto Cal) CD-6MC CD-12MC (Manual Cal)	Carbon Dioxide (CO ₂)	0-5,000 PPM	0, 600, 700, 800, 900, 1000, 1100... 2000... to 5000 PPM	0, 900, 1000, 1100...4000 ... to 5000 PPM	15 Years	900 - 5000 sq. ft.

** Replaceable Sensor



Since 1972 Macurco has been providing gas detection solutions for various applications. Macurco provides the highest quality gas detection solutions to customers worldwide.



Macurco Gas Detection
3601 N St. Paul Ave,
Sioux Falls, SD 57104

Phone: 1-877-367-7891

Website: www.macurco.com

Email: info@macurco.com