



**SILENT
KNIGHT**

by Honeywell

Model SD505-DUCTR and SD505-DTS-K

**Detect smoke in air handling systems and
prevent re-circulation with Silent Knight's
addressable duct smoke detector**

The SD505-DUCTR addressable duct smoke detector detects smoke and products of combustion present in air moving through an HVAC air handling system. The SD505-DUCTR is a heavy duty metal housing with a pre-installed SD505-APS photoelectric smoke detector and relay module. When smoke is detected in a duct, the unit communicates the condition to the IntelliKnight control panel. The panel, in turn, depending on programming and wiring, turns off fans, blowers, and other devices.

Now there's even more power and flexibility available to the IntelliKnight family of products. For more information on this product or to locate your nearest source, please call 800-328-0103.

Model SD505-DUCTR Analog Duct Smoke Detector with Relay Module

The Model SD505-DUCTR Addressable Duct Smoke Detector with Relay provides early detection of smoke and products of combustion present in air moving through an HVAC duct to prevent re-circulation of smoke into the air handling system. The SD505-DUCTR is a heavy duty metal housing with a pre-installed SD505-APS Analog Photo Electric Smoke Sensor and relay module. When smoke is detected in a duct, the unit communicates the condition to the IntelliKnight FACP. The built-in relay module, in turn, turns off fans, blowers, and other devices.

Operation

Air sampling is accomplished by two tubes which protrude into the duct. An exhaust tube of one standard length (7.5") is provided with the detector housing. Intake sampling tubes (ordered separately) are supplied in three standard lengths. Duct mounting is accomplished through a template and 4 sheet metal screws (provided).

Features

- Two-wire connection to SLC
- Detects and limits spread of smoke
- LED alarm indication and communication on sensor head
- Rugged steel backbox with clear plastic cover
- Installation template included
- No screens or filters to clean
- SD505-APS Photoelectric Smoke Detector pre-installed
- 3 standard tube lengths
- UL listed, complies with NFPA 72 and 101
- CSFM listed
- MEA Approved 429-92-E, Vol 9
- FM Approved

Specifications

Physical

Dimensions: 2¼" H x 9" L x 7¼" W
Weight: 3lbs

Electrical

Operating Voltage: 24 VDC
Alarm Relay Contact rating:
10A @ 24 VDC; 10A @ 115 VAC;
10A @ 240 VAC

Trouble Relay Contact Rating:
2.5A @ 30 VDC

Aux. Power Input Current:
20mA Standby, 62 mA Alarm
SLC Input Current: 0.5 mA
Max. SLS resistance: 50 Ohms



SD505-DUCTR



SD505-DTS-K

Environmental

Operating Temp: 32°F to 100°F
(0°C to 37°C)

Humidity: 10%-85% non-condensing

Other Ratings:

Air Velocity 300 - 4000 ft/min

Sampling Tubes:

SD505-T2	2.5ft sampling tube
SD505-T5	5ft sampling tube
SD505-T10	10ft sampling tube


Model SD505-DUCTR and SD505-DTS-K

Duct Smoke Detector with Relay and Remote Test Switch

Engineering Specifications

The air duct smoke detector shall be Silent Knight Model SD505-DUCTR and remote test switch shall be SD505-DTS-K. The housing shall contain a Silent Knight model SD505-APS, Photoelectric Smoke Sensor.

The duct detector shall be of metal construction. Complete mechanical installation must be able to be performed without removal of the detector cover. Terminal connections shall be screw type using a minimum of #6 screw.



**SILENT
KNIGHT**

by Honeywell

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice. For more information, contact Silent Knight 12 Clintonville Road, Northford, CT 06472-1610 Phone: (800) 328-0103, Fax: (203) 484-7118. www.silentknight.com

MADE IN AMERICA

FORM# 350005 Rev B
Copyright © 2011 Honeywell International Inc.